




Professional Dehumidifier for large and open spaces - Made in Sweden

WCD7HG Pro is a powerful professional dehumidifier that dehumidifies warehouses and industries. The working temperature range has been broadened using a new intelligent defrost system, i-EcoDefrost, from + 2 ° C up to + 35 ° C. i-EcoDefrost, developed and manufactured in Sweden, provides faster and better defrost and function, the machine becomes even more efficient, dehumidifies faster and more energy efficiently. The design of WCD Pro-series is well proven and has high reliability. This makes it reliable and easy to maintain. All exposed parts are adapted for use in aggressive environments.

The WCD Pro series is very energy efficient as it is based on the same principle as a heat pump. In the process of this professional dehumidifier, no unnecessary heat is extracted, since the same air is constantly circulating. Therefore, the method is easy to control and very energy efficient.

HG

Generally, units that have a defrosting function can operate at lower temperatures.

- Environmentally friendly refrigerant R290 
- Rotary compressor
- Removes excess moisture and bad odor.
- i-EcoDefrost, intelligent defrost system
- 3-row condenser
- professionals Dehumidification
- Easy to maintain.
- reliable
- The operating temperature range is right down to + 2C and up to + 35 ° C (32 ° C-40 ° C)
- Superior longevity
- Power saving
- Energy Efficient
- Quick defrost
- Adapted for aggressive environment.
- Made in Sweden



I-Eco Defrost HG-system is a technological innovation that is developed and produced in Sweden.

How it workd

- It senses room temperature and humidity and optimally operates the compressor system to enable the highest performance for capacity even at lower temperatures and humidity levels.

Specifikation - WCD7HG Pro

Max. working area	300 m ²
Air flow	129-296 m ³ /h
Capacity at 20°C & 70% RF	28 liter
Capacity at 30°C & 80% RF	46 liter
Power at 20°C & 70% RF	500 W
Power at 30°C & 80% RF	700 W
Working interval temp.	+2 till +30°C
Tank volume	11,4 liter
Fan speeds	2
Dimensions LxWxH	440x540x980 mm
Weight	38 kg
Noise level	54 dB*
Cooling media	R290 180g
Rated voltage	230V/50Hz
Protection class	IPX4
EAN code	7332857501052